

The SCF 20ft Flowback tank is a small and mighty solution for your on site water treatment and liquid sediment removal.

This tank has a 31,000 L capacity and is compliant for both road and rail transport allowing quick and easy deployment to almost any location.

Details

Managing on site water treatment has never been easier with our 20ft Flowback Tank.

It is built as an open top tank with a fold down gantry system, allowing operators to safely access the top of the tank and the central weir to treat water.

Our 20ft Flowback Tank has been designed for the purpose of removing suspended solids from water. The internal weirs encourage solids to drop from suspension and settle in the bottom of the tank, thanks to SCF's sediment removal system.

When the hard work is done, multiple drain points and the open top configuration make washing out the tank easy, so you can move on to the next job hassle-free.

Similar to our 40ft Flowback Tank and 45ft Flowback Tank, this tank can be connected in sequence together to allow for further separation and storage.

Key Features

- AS1657 compliant stair and hand rail system
- Inlet fitted with both Camlock and Bauer fittings as standard
- SCF clean flow overflow system fitted as standard
- Built-in weir system to assist in sediment separation
- Drain point at both ends

Options

- Customer co-branding
- Removabe hatches

Specifications 20ft Flowback Tank | FL20S Specifications may vary

Volume	
Litres	31,000
m^3	31

External		
Length (mm)	6,058	
Width (mm)	2,438	
Height (mm)	2,997	

Weight		
Tare (kg)	6,900	







